

POWERFLEX

MOTORIZED FLEXIBLE CONVEYORS



Type PF15

POWERFLEX

Rollers Ø 40mm

- Very robust Construction
- Drive capacity : 150 kg/metre
- Castors Ø 150x50 mm
- Standard roller pitch 127mm
Available options : pitch 76 and 102mm
- Bright zinc plated rollers Ø 40mm
- Adjustable height : 800 to 1100 mm
- Available in any length
- Speed regulation : from 5 to 60 cm/sec
- Electrical connection : single phase 220V

Type PF19

POWERFLEX

Rollers Ø 50mm

- Very robust Construction
- Drive capacity : 150 kg/metre
- Castors Ø 200x50 mm
- Standard roller pitch 127mm
Available options : pitch 76 and 102mm
- Bright zinc plated rollers Ø 50mm
- Adjustable height : 725 to 950 mm
- Available in any length
- Speed regulation : from 5 to 60 cm/sec
- Electrical connection : single phase 220V

Type PF15 POWERFLEX Rollers Ø 40mm

EXAMPLE	Lengths Expanded & Closed
Width 600 mm	14.6 m - 4.9 m 18.3 m - 6.1 m 19.6 m - 6.6 m 30.5 m - 10.2 m Any length available
Width 750 mm	14.6 m - 4.9 m 18.3 m - 6.1 m 19.6 m - 6.6 m 30.5 m - 10.2 m Any length available
Width 900 mm	14.6 m - 4.9 m 18.3 m - 6.1 m 19.6 m - 6.6 m 30.5 m - 10.2 m Any length available

Type PF19 POWERFLEX Rollers Ø 50mm

EXAMPLE	Lengths Expanded & Closed
Width 600 mm	14.6 m - 6.2 m 18.3 m - 7.8 m 19.6 m - 8.3 m 30.5 m - 13 m Any length available
Width 750 mm	14.6 m - 6.2 m 18.3 m - 7.8 m 19.6 m - 8.3 m 30.5 m - 13 m Any length available
Width 900 mm	14.6 m - 6.2 m 18.3 m - 7.8 m 19.6 m - 8.3 m 30.5 m - 13 m Any length available











C O N V E Y O R S

A DURAVANT COMPANY



Exclusive distributor
for the Benelux & France

UVO Tec BV

FMH CONVEYORS Benelux & France

Tel : +32.3.455.43.22 - Fax : + 32.3.454.36.70

Email : info@uvotec.eu www.uvotec.eu

WE HAVE SPECIFIC SOLUTIONS FOR YOUR APPLICATION
